

WALL-MAN[®] Paint Booth Personnel Lift

KEY FEATURES

- No contact with the floor
- Made to order
- Non slip floor in cage
- Three dimensional movement
- ATEX approved



Construction	Welded Steel
Finish	RAL 5015
Payload	150 kg (1 person plus equipment)
Controls	In cage: Up/Down; Left/Right; In/Out At ground Level: Up/Down
Air Supply	6 - 8 bar. 350 litres per minute supplied via hoses on self-retracting hose reels. A compressed air outlet for air tools is provided in the cage.
Key Dimensions	<ul style="list-style-type: none"> Height of raised platform: 3275 mm <i>(may be increased to a maximum of 4525 mm or reduced as required)</i> Height to top of upper rail: 4170 mm <i>(may be increased to a maximum of 5420 mm or reduced in line with raised platform height)</i> Distance from wall to front of cage: 1285 mm <i>(fully retracted)</i> 2585 mm <i>(fully extended)</i> Cage size (W x D): 900 x 820 mm.
Installation	The platforms are suspended from the upper rail which is fitted to the booth at high level. The bottom guide wheels run on a flat strip at the base of the booth walls and exert horizontal forces only. There is no direct contact with the floor.
Imposed Loads	<i>The following data relates to the standard model only. For platforms with height or off-set variations; please ask for specific information.</i> <ul style="list-style-type: none"> Upper Rail, Vertical Load: 460 kg Lower Rail, Vertical Load: 0 kg Upper Rail, Horizontal Load: 159 kg Lower Rail, Horizontal Load: 159 kg
Drawings	

